

PRODUCT CATALOG



Video Intercom Panel

BLUETOOTH ACCESS CONTROL



PHONE



FOB



VIDEO
INTERCOM

FEATURES

Plug and Play – No Programming

Works with the Smart Door/Gate Controller

Vandal-Resistant Touchscreen

IP65, IK10

Temp/Humidity: -22°F(-30°C) to 140°F (60°C) / 10-90% Non-Condensing

Power Input: 802.3 at PoE+

Dimensions: 13.8" x 5.1" x 2.1" (350 x 130 x 53.9 mm)

Weight: 5.0 lbs (454 grams)

HOW TO ORDER

SERIES
INT-P

Series

INT-P

Entegri
Smart Property
Systems



Smart Deadbolt

BLUETOOTH ACCESS CONTROL



PHONE



FOB



VIDEO
INTERCOM

FEATURES

No Network Required, Encrypted Bluetooth Security

Battery Life Up to 2 Years (4 AA Batteries, Not Included)

9V Battery Backup for Emergency Unlock

ANSI Grade 2, IP55

Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing
UL/cUL 10c 3-hour

ADA Compliant

Inside Lock/Unlock: Thumb Turn

Outside Lock/Unlock: Smartkey or VIZpin Fob

Adjustable Door Thickness: 1 3/8" to 1 3/4"

Door Prep: 1" Bore / 1 1/8" x 2 3/4" Rounded Strike / 1" X 2 1/4"
Rounded Faceplate

Adjustable Backset: 2 3/4" and 2 3/8"

ARCHITECTURAL FINISHES

B
Black Matte
631/US19

N
Nickel
619/US15

HOW TO ORDER

SERIES	FINISH	BACKSET
VPDB	B N	ADJ

Series VPDB

Entegriety Smart Property Systems



EXTERIOR VIEW



INTERIOR VIEW

Smart Door/Gate Controller

Series
VP2

BLUETOOTH ACCESS CONTROL



PHONE



FOB



VIDEO
INTERCOM

FEATURES

Up to 30' Read Range

No Network Required, Encrypted Bluetooth Security

Mounts on the Inside, Away from Vandals and Weather

Controls Door Strikes, Mag Locks or Gates

IP54

Temp/Humidity: -40F° (-40°C) to 150°F (66°C) / 0-95% Non-Condensing

Power Input: 12VDC, 20mA Average

Relay: 750mA 12-24 VAC/VDC

Outside Unlock: Smartkey or VIZpin Fob

Dimensions: 4.0" x 1.3" x 0.8" (101 x 34 x 20 mm)

Weight: 1.6 oz (46 grams)

FCC & CE

HOW TO ORDER

SERIES
VP2

Entegriety
Smart Property
Systems



FRONT VIEW



BACK VIEW

Smart Lever Set

BLUETOOTH ACCESS CONTROL



PHONE



FOB



KEY



VIDEO
INTERCOM

FEATURES

- No Network Required, Encrypted Bluetooth Security
- Battery Life: Up to 2 Years (4 AA Batteries, Not Included)
- Interchangeable SFIC Core
- ANSI Grade 1, IP54
- Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing
- UL/cUL 10c 3-hour
- CC A117 and ADA Compliant
- Inside Unlock: Unimpeded Egress
- Outside Unlock: Smartkey, Physical Key or VIZpin Fob
- Adjustable Door Thickness: 1 3/8" to 2"
- Door Prep: 2 1/8" Cylindrical Bore
- Backset: 2 3/4" or 2 3/8"

ARCHITECTURAL FINISHES

<p>S Stainless 626/US26D</p>	<p>B Black Matte 631/US19</p>	<p>N Nickel 619/US15</p>
---	--	---

LEVER DESIGNS



PORTFOLIO – P



SILHOUETTE – S

HOW TO ORDER

SERIES	FINISH*	BACKSET	LEVER*	STRIKE
VPSLC	S B N	1 - 2-3/4" 1x - 2-3/8"	P S	ANSI - ANSI FL - Full Lip (residential)

**Custom lever designs and finishes available by special order.*



Series VPSLC

Entegrity Smart Property Systems



EXTERIOR VIEW



INTERIOR VIEW

EntegritySmart.com
Sales@EntegritySmart.com
717-327-4244

Smart VIZITOR Keypad

BLUETOOTH ACCESS CONTROL



PHONE



FOB



VIDEO
INTERCOM

FEATURES

Plug and Play – No Programming

Works with the Smart Door/Gate Controller

Permanent or One-Time VIZITOR Codes

IP66

Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing

Power Input: 12VDC, 80mA Average

Rugged, Anti-Vandal Zinc Alloy Case

HOW TO ORDER

SERIES
KEYPADM

Series KEYPADM

Entegri
ty
Smart Property
Systems



Smart Solar Kit

Series
VPS

BLUETOOTH ACCESS CONTROL



PHONE



FOB



VIDEO
INTERCOM

FEATURES

- Saves on Electrical Installation
- Controls 12VDC Door Strikes
- Runs Up to 3 Days with No Sunlight
- IP65
- Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing

Kit Includes:

- Smart Door/Gate Controller
- 12VDC Solar Controller
- 20 Ah Battery
- IP65 UV Enclosure
- Mounting Hardware for Up to 4" Pole
- 15' Panel Cable, 18' Door Strike Cable

HOW TO ORDER

SERIES
VPS

Entegrity Smart Property Systems



SOLAR ENCLOSURE



SOLAR PANEL

Smart Long-Range Bluetooth Reader

BLUETOOTH ACCESS CONTROL



PHONE

FEATURES

Up to 30' Read Range

No Network Required, Encrypted Bluetooth Security

Easy to Upgrade Existing Access Control Systems

Mounts on the Inside, Away from Vandals and Weather

IP54

Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing

Power Input: 12VDC, 20mA Average

Outside Unlock: Smartkey

Dimensions: 4.0" x 1.3" x 0.8" (101 x 34 x 20 mm)

Weight: 1.6 oz (46 grams)

FCC & CE

HOW TO ORDER

SERIES
VP2x

Series

VP2x

Entegri
ty
Smart Property
Systems



FRONT VIEW



BACK VIEW



EntegriSmart.com
Sales@EntegriSmart.com
717-327-4244

Smart Crash Bar

Series 6WS-VZ

BLUETOOTH ACCESS CONTROL



PHONE



FOB



KEY



VIDEO
INTERCOM

FEATURES

No Network Required, Encrypted Bluetooth Security

Battery Life Up to 2 Years (4 AA Batteries, Not Included)

ANSI/BHMA A156.115 Grade 1, IP54

Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing

UL/cUL 10c 3-Hour

CC A117 and ADA Compliant

Inside Unlock: Unimpeded Egress

Outside Unlock: Smartkey, Physical Key or VIZpin Fob

Adjustable Door Thickness: 1 3/4" to 2"

Door Prep: ANSI A115.1

Backset: 2 3/4"

For use with 6300 Series Rim, Surface and Concealed Vertical Rod Exit Devices

ARCHITECTURAL FINISHES

Satin Stainless
Steel
630 (US32D)

HOW TO ORDER

SERIES	FAMILY	LEVER*	TYPE	FINISH*	HANDING
6WS	VZ	PHL	R-Rim Vertical Rod V-Surface C-Concealed	630	RH** LH

*Custom lever designs, keying and finishes available by special order
**Handed but field reversible.

Entegrity Smart Property Systems



EXIT TRIM



EXIT DEVICE



EntegritySmart.com
Sales@EntegritySmart.com
717-327-4244

Smart Interconnected Lock

BLUETOOTH ACCESS CONTROL



PHONE



FOB



KEY



VIDEO
INTERCOM

FEATURES

- No Network Required, Encrypted Bluetooth Security
- Battery Life Up to 2 Years (4 AA Batteries, Not Included)
- ANSI/BHMA Grade 2, IP54
- Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing
- UL/cUL 10c 20-Minute
- CC A117 and ADA Compliant
- Inside Unlock: Thumb Turn
- Outside Unlock: Smartkey, Physical Key or VIZpin Fob
- Adjustable Door Thickness: 1 3/8" to 1 3/4"
- Door Prep: 4" or 5 1.2" Center to Center
- Adjustable Backset: 2 3/4" and 2 3/8"

ARCHITECTURAL FINISHES

Satin
Chromium
626 (US26D)

Flat
Black
622 (US19)

HOW TO ORDER

SERIES	FAMILY	LEVER*	FINISH*	HANDING	BACKSET	STRIKE
CLS	VZ	PHL	626 622	RH** LH	ADJ	ASA - ANSI/ASA FL - Full Lip (residential) T - "T" Strike

*Custom lever designs, keying and finishes available by special order
**Handed but field reversible.

Series CLS-VZ

Entegriety Smart Property Systems



EXTERIOR VIEW



INTERIOR VIEW

Smart Mortise Lock

BLUETOOTH ACCESS CONTROL



PHONE



FOB



KEY



VIDEO
INTERCOM

FEATURES

- No Network Required, Encrypted Bluetooth Security
- Battery Life Up to 2 Years (4 AA Batteries, Not Included)
- ANSI/BHMA A156.115 Grade 1, IP54
- Temp/Humidity: -40°F (-40°C) to 150°F (66°C) / 0-95% Non-Condensing
- UL/cUL 10c 3-Hour
- CC A117 and ADA Compliant
- Inside Unlock: Lever or Thumb Turn
- Outside Unlock: Smartkey, Physical Key or VIZpin Fob
- Adjustable Door Thickness: 1 3/4" to 2"
- Door Prep: ANSI A115.1
- Backset: 2 3/4"

ARCHITECTURAL FINISHES

Satin Stainless Steel
630 (US32D)

Flat Black
622 (US19)

HOW TO ORDER

SERIES	FAMILY	FUNCTION	LEVER*	TRIM	FINISH*	HANDING	BACKSET	STRIKE
MRS	VZ	116 - Entrance 136 - Dormitory/ Exit	PHL	F-TRIM Round Rose	630 622	RH** RHR LH LHR	234 - 2-3/4"	ASA - ANSI/ASA

*Custom lever designs, keying and finishes available by special order
**Handed but field reversible.

Series MRS-VZ

Entegrity Smart Property Systems



EXTERIOR VIEW



INTERIOR COMPONENT



ENTEGRITY SMART PROPERTY SYSTEMS

ENTEGRITYSMART.COM

Sales@EntegritySmart.com

717-327-4244